# Under-Counter Glasswasher G30 台下式洗杯机 G30

## 特点及优势:

- 内置清洁剂分配器和催干剂分配器,且易于连接;
- •专业洗涤系统:旋转主洗臂、强动力主洗泵和大容量水箱;
- 附加冷水喷淋程序冷却可使用的啤酒杯;
- •控制面板简单易操作;
- •不锈钢双层坚固平衡门,安全塑料把手;
- 主要装置和零部件(进水电磁阀、加热包、控制面板、清洁剂分配器和催干剂分配器)
  便于使用、维修和保养





#### **Characteristics and Advantages**

- Detergent and rinse aid dispensers for easy connection to the external chemical source
- Washing system endowed with rotating washing arms, powerful wash pump and large wash tank for professional washing
- Extra program to cold rinse beer glasses providing sanitized cool glasses
- Simple operation control panel
- Solid double skinned counter-balance stainless steel door with hurt-free handle in plastic
- Easy service access to main components (inlet valve, boiler heating elements, control panel components, rinse aid pump and/or detergent pump) without moving the unit

技术参数 Technical Data		
名称/型号	Name/Model	G30
电源要求	Power requirements	220V/50Hz/1N
外形尺寸	External dimension (mm)	700x495x456
洗涤周期	Wash cycle (s)	120
洗涤筐数	Max capacity (rack/hour)	30
最大洗涤高度	Clearance height (mm)	290
总功率	Total connected load (kW)	2.7
漂洗加热功率	Booster heater (kW)	2.5
水槽加热功率	Tank heater (kW)	2
清洗水泵功率	Wash pump (kW)	0.2
进水压力	Incoming water pressure (bar)	2 - 5
进水温度	Incoming water temperature (°C)	10 - 65
升温器容量	Booster capacity (I)	2.5
进水管径	Diameter of water inlet hose (in)	<sup>4</sup> / <sub>3</sub>
洗涤温度	Wash temperature (°C)	60
水箱容积	Wash tank capacity (I)	16
漂洗温度	Rinse temperature (°C)	82
热水喷淋循环耗水量	Hot water spray consumption (I)	2
净重	Net weight (Kg)	35
噪音	Noise (dB)	61







选装件 Optional Accessories		
方形洗杯筐	Square cup washing basket	1 (400x400x110mm)
分隔器	Divider	1 (290x290x75mm)
方形刀叉筐	Square knife and fork basket	1 (89x113x113mm)


### 安装接驳要求 Installation and Connection Requirements


• 电力安装需要220V/50Hz/1N,外部需加装独立的空气开关


• 机器可直接与一般供水系统连接,最低水压须达到2Kg/cm<sup>2</sup>

• Power requirements: 220V/50Hz/1N + Ground with a separate external circuit breaker

• The machine can be directly connected to water supply system. The lowest incoming water pressure should be 2Kg/cm<sup>2</sup>







₩I = 进水管径3/4
 GD = 排水管径
 EI = 电源输入
 XD = 洗涤剂安装入口
 XR = 催干剂安装入口
 EQ = 等电位螺丝(接地)

#### 主要使用场所 Ideal for:

- •小型餐厅、咖啡厅、酒吧等场所;
- Small restaurants, coffee shops, bars and other catering industries